COLMAN et al Appl. No. 10/510,441 March 2, 2008

RECEIVED CENTRAL FAX CENTER

MAR 0 3 2008

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1-10 (cancelled).

- 11 (currently amended). A grid having the form of a web of vertically disposed plates, said web of plates comprising:
- (a) a network of strands of plate segments connected by junctions, said strands terminating only at the periphery of the grid, and
 - (b) one or more internal plate branches,

each plate segment being joined at one end to a junction with at least two other plate segments and at the other end either being joined to a junction with at least two other plate segments or terminating at or near the periphery of the grid, said internal plate branch comprising a plate having a free end within the grid and being joined at one end thereof to a segment or to another branch, wherein in horizontal cross-section through the grid each segment has at least two angular portions, at least two curved portions or at least two angular and curved portions, which portions alternate in direction.

COLMAN et al Appl. No. 10/510,441 March 2, 2008

12 (previously presented). A grid according to claim 11 wherein the alternation in direction of the angular or curved portions is of equal magnitude or of differing magnitude.

13 (previously presented). A grid according to claim 11 wherein the grid is formed from vertical plates wherein each vertical plate has a high resistance to deformation in a direction parallel to its vertical plane and is relatively easily deformed in the horizontal plane.

14 (previously presented). A grid according to claim 11 wherein the grid is free from a solid boundary perimeter plate.

15 (previously presented). A grid according to claim 11 wherein the grid is formed from a metal.

16 (previously presented). A grid having the form of a web of vertically disposed interconnected plates or strips, said web having in horizontal cross-section a repeating pattern, said pattern comprising one or more series of unit cells, each cell having substantially polygonal shape wherein each polygon contains at least 8 sides, at least two internal angles above 180° and at least four internal angles below 180°.

17 (previously presented). A grid according to claim 16 wherein one or more linear or branched internal projections is provided on one or more sides of a polygon or

COLMAN et al Appl. No. 10/510,441 March 2, 2008

at the junction of two sides of a polygon, wherein the said projections do not bridge any polygon.

18 (previously presented). A grid according to claim 16 wherein the grid is formed from vertical plates wherein each vertical plate has a high resistance to deformation in a direction parallel to its vertical plane and is relatively easily deformed in the horizontal plane.

19 (previously presented). A grid according to claim 16 wherein the ratio of the height of the web to the average thickness of the vertical plates forming the web lies in the range 100:1 to 2:1.

20 (canceled).

21 (currently amended). A grid according to claim 20 16 wherein the geometric shape of the polygon is superimposed on itself when rotated in the horizontal plane through 90°, or through 180° or through 120°.

22 (previously presented). A grid according to claim 13 wherein the grid is free from a solid boundary perimeter plate.

23 (previously presented). A grid according to claim 13 wherein the grid is formed from a metal.